



# TesMan Remote Loader

Revolutionary technology to quickly and safely clean, inspect and load using remote control and remote monitoring.

Stop



Setup

Depth 1: 2.8 ft / -0.5 ft

<input type="checkbox"/>	Temperature	80.25
<input checked="" type="checkbox"/>	Depth 1	155
<input type="checkbox"/>	Depth 2	-80
<input type="checkbox"/>	Four	0.00

Record

Record

# TesMan Remote Loader (SP-TRL)

Get more productivity from your mobile equipment.

The **TesMan Remote Loader** is a lightweight, multi-purpose unit that easily adapts to your underground mobile equipment through our customizable **Quick-Connect** attachment system. By incorporating a simple locking pin assembly, the installation and removal of the SP-TRL is an easy two-minute process for one person.

## Installing a TRL is like getting six machines in one!

- Cleans 100% of plugged holes of water and broken ground
- Auger attachment cleans lifters and lower holes
- Accurately maps 100% of short-drilled holes and location
- Operator's screen displays and records endoscopic inspection of holes – allowing for two-way communication through a comments page
- Loads bulk emulsion, ANFO, or stick products, plus electric and non-electric caps
- Communication Station and Dashboard
- Screen cutter attachment cuts without removing essential ground control



Customizable **Quick-Connect** attachment system

## Improve productivity:

- Compact and lightweight - weighs less than 600 lbs (270 kg)
- Adaptable to almost any piece of mobile equipment
- Tremendous flexibility - 80 degrees vertical movement, 100 degrees horizontal motion, and everything in between
- Will clean and load a 20 ft x 20 ft (6m x 6m) round with standard boom; up to 70 holes in two hours
- Longer boom lengths available
- Accurate mapping and drill hole depth feedback
- Up to 10% improvement in advance, better cap sequencing, and less loose on the face
- Camera provides a magnified image on the screen
- Screen Cutter attachment cuts openings in screening without removing essential ground control

## Safety at the face:

- Operator stays secure at least 17 ft (5 m) from the face with standard boom and never has to approach the face
- Operator never has to approach the face
- Clean and load as fast, if not faster, than by hand
- Avoids repetitive strain injuries of twisting, turning, digging and cutting

Dealer:

**MINECAT**<sup>®</sup>

Manufactured by:  Industrial  
Fabrication Inc.

[www.minecat.com](http://www.minecat.com)

+1.705.523.1621